




Mounting Instructions

1. Install enclosed mounting clips to surface with the supplied screws
2. Snap or slide the fixture into the mounting clips. (Handle with care to avoid breaking the lamps)
3. Connect the enclosed power cord to the end of the fixture. (marked "IN") Plug the cord into either a 120v or 230v outlet. The maximum distance to the outlet should be 5 feet.


Adding Fixtures

Multiple fixtures can be linked together for continuous runs with the enclosed 12" connector cable. Do not connect more than 200w per string.



Lamp Replacement

1. Turn off or unplug the fixture.
2. Remove the old lamp by rotating the lamp ¼ turn so the lamp pins are aligned in the slots of the lamp holder.
3. Pull the lamp out of the holders.
4. Insert a new lamp by aligning the lamp pins with the slots of both lamp holders, and then gently pushing lamp in. *Note: replace only with a T5 (8w, 13w, 21w, 28w) lamp.*
5. Rotate the lamp ¼ turn to secure the pin contacts into both lamp holders. (You will feel the pins lock into place)



Safety Precautions

1. Read all safety precautions and installation instructions carefully before installing or servicing this fixture. Failure to comply with these instructions could result in potentially fatal electric shock and/or property damage. Do not handle an energized fixture or attempt to energize any fixture with wet hands or while standing on a wet or damp surface or in water. Make sure that the power source conforms to the requirements of the fixture. (*see labels on fixture housing*).
2. This portable lamp fixture has a polarized plug (one blade is wider than the other) to reduce the risk of electrical shock. This plug will fit in a polarized outlet only one way. If the plug does not fit fully in the outlet, reverse the plug. If it still doesn't fit, contact a qualified electrician. Never use with an extension cord unless the fixture plug can be fully inserted into the extension cord. Do not alter the fixture plug.
3. Additional cautions:
 1. Do not use a dimmer switch of any kind.
 2. Do not install over a heat source.
 3. Do not install directly over water.
4. To reduce the risk of fire, electric shock or injury to persons:
 1. Use only insulated staples or plastic ties to secure cords.
 2. Route and secure cords so that they will not be pinched or damaged.
 3. Position the portable cabinet light with respect to the cabinet so the lamp replacement marking can be read during relamping.
5. Injury to persons and damage to the mounting surface may result if the fixture or mounting hardware is pulled from the mounting location. To reduce the possibility of such injury, be sure to mount the fixture only on a surface that is structurally sound. (*see mounting instructions*) This fixture is intended for use as general indoor lighting in dry locations only.